Mobile AI Cube BAI-1902



KFY FFATURES



- Nvidia GPU Certified
- AMD EPYC™ 7000 Series Processor
- Up to 4 GPUs
- LSI RAID Controller w/CacheVault
- 1200W to 1600W Platinum PSU
- · Tool-less top cover design
- Strong carrying handles
- · Pelican case
- MB Slide Drawer design supports smooth integration and user friendly after service
- System health & information bank display provides excellent checkup and after service follow up
- Short chassis depth, 345mm/13.6", can easily deploy into office to fulfill Al application demands w/o RACK
- 3 Year Warranty



GPU TESTED/CERTIFIED

Bison Computing Mobile GPU Computing Server solution is tested and certified to operate with up to QUAD industry leading Nvidia® GPU cards optimized for ML/DL applications.

DOD CERTIFICATION

Bison Computing Mobile Servers are DoD Network Certified and TAA Compliant.

Bison Computing Deep Learning/Machine Learning solution is an 'ALL-IN-ONE' solution. Combining the power of up to 4 GPU cards with high density mix storage – 9x 3.5"+ 10x 7mm 2.5" fulfill Al, ML, DL demands.

CACHEVAULT BATTERY RAID CARD 4 x GPU

120X38 FAN

CHASSIS CUSTOMIZATION

Well thermal design provide efficient heat mitigation in tactical operational environment. The custom design provides optimal thermal condition for GPU server.







Detailed Specs and Features of the Mobile Al Cube

45mm x 345mm x 235mm 8 lbs. MD EPYC™ 7000 Series Processor Family ingle Socket SP3 (LGA4094) MD EPYC™ 7601 32 Core 64 Threads DIMM slots Up to 512GB (8x 64GB DDR4 RDIMM) upports DDR4 2666/2400/2133 LR DIMM, R DIMM and ECC DIMM 1.2V ystem ID ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface foliage Reference an Speed Sensor femperature Sensor
MD EPYC™ 7000 Series Processor Family ingle Socket SP3 (LGA4094) MD EPYC™ 7601 32 Core 64 Threads DIMM slots Up to 512GB (8x 64GB DDR4 RDIMM) upports DDR4 2666/2400/2133 LR DIMM, R DIMM and ECC DIMM 1.2V ystem ID ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface foltage Reference an Speed Sensor
ingle Socket SP3 (LGA4094) MD EPYC™ 7601 32 Core 64 Threads DIMM slots Up to 512GB (8x 64GB DDR4 RDIMM) upports DDR4 2666/2400/2133 LR DIMM, R DIMM and ECC DIMM 1.2V ystem ID ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface 'oltage Reference an Speed Sensor
DIMM slots Up to 512GB (8x 64GB DDR4 RDIMM) upports DDR4 2666/2400/2133 LR DIMM, R DIMM and ECC DIMM 1.2V ystem ID ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface 'oltage Reference an Speed Sensor
upports DDR4 2666/2400/2133 LR DIMM, R DIMM and ECC DIMM 1.2V ystem ID ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface foltage Reference an Speed Sensor
ystem Alert LED AN Power LED ystem HDD Activity LED ystem Power LED ystem Information letwork Interface 'oltage Reference an Speed Sensor
letwork Interface foltage Reference fan Speed Sensor
ower On/Off ystem ID ystem Reset x USB
xternal 9x 3.5" HDD hot-swap 90TB raw storage (9x 10TB HDD) 8x 7mm 2.5" SSD hot-swap 16TB high performance storage (2x 2TB SSD)
nternal 2x 7mm 2.5" 4TB (2x 2TB SSD) Boot drives
SI 9361-24i SATA/SAS High Port Count 12Gb/s RAID Controller SI CacheVault for LSI 9361-24i AID 0/1/5/6/10/50/60
x 1-port SAS/SATA backplane x 4-port SAS/SATA backplane
x PCI-E 3.0 x16 slots x PCI-E 3.0 x8 slots x PCI-E 3.0 x4 M.2 ports x Oculinkx4
28Mb SPI AMI BIOS® .CPI 5.1, SMBIOS 3.1.1, Plug-and-Play (PnP), BIOS Rescue Hot-key, RTC (Real Time Clock) Vake Up, Riser Card Auto-Detection Support
x COM serial port x D-Sub VGA port x USB 3.0 ports x RJ45 10G base-T x RJ45 dedicated IPMI LAN port AN ports with LED (ACT/LINK LED and SPEED LED)
200W / 1600W 1+1 redundant PSU 80+ Platinum
x 120X38mm hot-swap fans x 80X38mm hot-swap fans
SPEED AST2500 x Realtek RTL8211E for dedicated management SLAN Watch Dog IMI
lp to 4x Nvidia GPU cards Options: Quadro GV100, Quadro P6000, Quadro GP100, Titan XP, others
luggedized design for expeditionary operation and harsh environment tainless steel hash lift handle flush mounted on each side of the chassis for safe lifting
00-240V~, 50/60Hz, 12A
°C ~ 35°C
Tabling, pre-load Centos, Pelican transport case
YYX



Bison Computing, LLC delivers Deep Learning Solutions leverage Nvidia GPU, high performance, high availability storage solution and robust management tools required for today's data-intensive applications. We are reliable and cost-effective storage solutions encompass IP-SAN storage solutions that support Fiber Channel (FC), Serial Attached iSCSI (SAS) and Serial ATA (SATA) storage interfaces.



1121 Westrac Dr, Suite 106 Fargo, ND 58103



sales@valleyit.com